
STAINLESS STEEL SPRING RETRACTABLE HOSE REELS




SS SERIES


LESS HOSE							
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	INDEX	
P SERIES							
P-LPL-335-SS	3⁄8"	1/2"	35	300	34	1	
P-LPL-350-SS	3⁄8"	5⁄8"	50	300	39	1	
P-LPL-425-SS	1⁄2"	3⁄4"	25	300	39	2	
SH & MP SERIES							
SHL-N-350-SS	3⁄8"	5⁄8"	50	300	44	3	
SHL-N-450-SS	1⁄2"	3⁄4"	50	300	46	3	
SHL-N-525-SS	3⁄4"	11⁄16"	25	300	45	4	
MPL-N-350-SS	3⁄8"	¹¹ ⁄16"	50	3,000	53	3	
MPL-N-450-SS	1⁄2"	¹³ ⁄16"	50	2,500	53	3	
T SERIES							
TSHL-N-350-SS	3⁄8"	5⁄8"	50	300	55	5	
TSHL-N-375-SS	3⁄8"	5⁄8"	75	300	73	6	
TSHL-N-3100-SS	3⁄8"	5⁄8"	100	300	74	6	
TSHL-N-450-SS	1/2"	3⁄4"	50	300	55	5	
TSHL-N-475-SS	1/2"	3⁄4"	75	300	71	6	
TSHL-N-4100-SS	1/2"	3⁄4"	100	300	80	6	
TSHL-N-550-SS	3⁄4"	11/16"	50	300	70	7	
TMPL-N-3100-SS	3⁄8"	¹¹ ⁄16"	100	3,000	82	6	
TMPL-N-4100-SS	1⁄2"	¹³ ⁄16"	100	3,000	80	6	
EN SERIES							
ENL-N-335-SS	3⁄8"	5⁄8"	35	300	46	8	
ENL-N-350-SS	3⁄8"	5⁄8"	50	300	58	9	
ENL-N-425-SS	1⁄2"	3⁄4"	25	300	63	8	
ENL-N-450-SS	1/2"	3⁄4"	50	300	61	9	
ENML-N-335-SS	3⁄8"	11/16"	35	3,000	64	8	
ENML-N-350-SS	3⁄8"	11/16"	50	3,000	80	9	
ENML-N-425-SS	1/2"	¹³ ⁄16"	25	2,500	61	8	
ENML-N-450-SS	1/2"	13⁄16"	50	2,500	82	9	

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Х	Y	М	N
1	6 ³ ⁄4"	185⁄8"	17 ¹ ⁄8"	6"	6"	4"	5"
2	7"	185⁄8"	171⁄8"	6"	6"	4"	5"
3	81⁄4"	211⁄4"	191⁄2"	6"	6"	4"	5"
4	93⁄8"	211⁄4"	191⁄2"	6"	6"	4"	5"
5	9 ³ ⁄8"	21 ¹ ⁄4"	19 ¹ /2"	8"	9"	7"	8"
6	9 ³ ⁄8"	25 ¹ ⁄2"	24"	8"	9"	7"	8"
7	97⁄8"	251⁄2"	24"	8"	9"	7"	8"
8	67⁄8"	187⁄8"	19"	6"	6"	4"	5"
9	81⁄2"	213⁄4"	217⁄8"	6"	6"	4"	5"
	Overall Dimensions			Base		Mounting Pattern	









SS SERIES - SPRING .: REEL SPECIFICATIONS

SS-T Series

SWIVEL

- · Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- · Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- · Electro-polished stainless steel finish
- · Each of these reels is built of their standard series with their own unique features & benefits

RETRACTION

- · See page 11 For P Series spring driven features
- See page 12 For SH & MP Series spring driven features
- · See page 13 For T Series spring driven features
- See page 14 For EN Series spring driven features

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

Corrosive Environments

Hygienic Environments

- Medical Services
- Marine/Docks/Offshore
- · Manufacturing Plants & Facilities
- Pulp & Paper Plants
- Food & Chemical **Processing Plants**
- · Bottling Plants

ACCESSORIZE YOUR REEL :: PG 52

- O-Rings & Swivels
- Mounting Brackets
- Assorted Reel Accessories



· Grocery Stores

Dairies

 Restaurants & Commercial Kitchens

Meat Packing

- Water Treatment & Supply
- Petrochemical
- Food Grade Washdown



